

B1
A1
Cont.
a bracket attachable to the bridging member at any of a plurality of locations; and

at least one notch formed in said bracket such that when said bracket is attached to said bridging member, at least one said notch extends at an incline to the elongated axis thereof.

✓ Please cancel claims 2 and 3 without disclaimer or prejudice.

Please amend claims 4, 6-10, 15, 21 and 22 as follows:

A2
Sub B2
4. (Amended) The stud bridging/spacing member of claim 1, wherein said notches extend inwardly at an angle of about five and a half degrees to about eight degrees relative to a perpendicular to the longitudinal axis.

Sub B3
6. (Amended) The stud bridging/spacing member of claim 1, wherein the notches incline in the same direction.

A3
7. (Amended) The stud bridging/spacing member of claim 1, wherein the notches have a width of about 0.065 inch (0.16 cm) to 0.080 inch (0.20 cm).

8. (Amended) The stud bridging/spacing member of claim 1, wherein the notches have a width of 0.080 inch (0.20 cm).

9. (Amended) The stud bridging/spacing member of claim 1, wherein the sides of the notches are parallel.

B3

Q3
Cont.

10. (Amended) The stud bridging/spacing member of claim 1, wherein the sides of the notches are straight.

Sub
B4

15. (Amended) The stud bridging/spacing system of claim 14 wherein each said stud-engaging notch in said first lateral side and each said other stud engaging notch in said second lateral side extends at an incline to the longitudinal axis of said bridging member.

Sub
B5

21. (Amended) A stud bridging/spacing system for laterally supporting a plurality of spaced-apart studs each having a web, comprising:

means for spanning between the webs of at least two spaced-apart studs, said means for spanning having a substantially V-shaped cross-sectional shape; and

means for engaging the webs of the at least two spaced-apart studs, said means for engaging having a substantially V-shaped cross-sectional shape and being removably affixable to said means for spanning in a plurality of locations therealong.

22. (Amended) Apparatus for laterally supporting a plurality of spaced-apart studs each having a web, said apparatus comprising:

an elongated bridging member having two ends;

a stud engager formed in said elongated bridging member; and

a face bracket attachable to a vertical surface and attachable to one end of said elongated bridging member, said face bracket having a pair of first portions which are angled to

Q5 B5
Cont.

approximate said cross-sectional shape of said elongated bridging member and a pair of second portions which extend at right angles to said pair of first portions and are attached thereto.

Please cancel claims 25 and 26 without disclaimer or prejudice.

Please amend claims 27, 33 and 37 as follows:

Q6

Sub
B67

27. (Amended) The apparatus of claim 22 wherein said elongated bridging member has a cross-sectional V-shape.

Sub
B77

33. (Amended) A metal stud wall comprising:
at least two metal studs each having at least two flanges interconnected by a web, the web of each stud having an opening and the studs being arranged in a row with the openings in the webs thereof aligned with one another;
an elongate member spanning between the webs of at least two studs, said elongate member having a substantially V-shaped cross-sectional shape;
a first bracket having a substantially V-shaped cross-sectional shape and being attached to said elongated member;
at least one stud engager in said first bracket for engaging the web of one metal stud;
a second bracket having a substantially V-shaped cross-sectional shape and being attached to said elongated member; and

Q7

Q7
Conte B7

at least one other stud engager in said second bracket for engaging the web of
another stud.

Sub
B8

37. (Amended) A wall arrangement comprising:

first vertical surface means;

second wall means perpendicularly extending from said first vertical surface
means, said second wall means formed from a plurality of spaced-apart metal studs each having a
web portion;

means for spanning from said vertical surface through an opening in the web of
one said metal stud;

means for retainingly engaging said web of said one metal stud, said means for
retainingly engaging said web of said one metal stud on said means for spanning; and

means for attaching said means for spanning to said vertical surface of said first
wall.

~~Please cancel claims 38-41 and 44 without disclaimer or prejudice.~~

REMARKS

I. Election and Amendments

In the Official Action, the Examiner stated that restriction to one of the following
inventions is required under 35 U.S.C. § 121:

- I. Claims 1-32, 33-37 and 42-43 drawn to a stud bridging system, wall arrangement
and method of constructing, classified in class 52, subclass 712 and class 52,